


Kidd

Bale Chopper

806. 807.



Bale Chopper Kidd 806. 807.

Simple, Versatile, Durable and Affordable

*Bedding,
Feeding
& Mulching
no problem!*

Straw for Bedding and Mulching

- Better use of material and labour with less wastage
- Accurate placement of bedding at front of stalls
- Cleaner and healthier bedding and animals
- Increased moisture absorption
- Easier use in liquid slurry systems
- Variable chop length for different Poultry beddings
- Good availability of an economically sourced bedding material
- Straw has no chemical treatments applied to it



Straw and Hay for Feeding

- Less waste
- Increased palatability
- No selective feeding
- Increased Digestibility
- Higher live weight gains





Standard Features

- Minimal service and running costs
- Discharge ports on both sides of the machine
- Simple operation from inside the tractor
- Hydraulically driven adjustable rotating tub
- Versatile 'Quick Hitch' A Frame linkage or fully Trailed version available
- Heavy Duty bevel gearbox requires minimised power requirement
- PTO shaft with Slip Clutch overload protection
- Quality painted finished achieved with a fully shot-blast preparation
- Segmented tub panels for easy replacement
- Rear parking stand for stability
- Chain Driven
- Hydraulic Bale Lift for easy chopping start-up
- Load Bearing Wheels



Optional features

- High Level Discharge Kit (min height 3m) **
- Mulching chutes for soft fruit and landscaping
- Additional Blade Kit
- Short Chop Kit
- 1:2 Gearbox
- Large Rectangular Bale Kit
- Bedding Chutes
- Swan Neck Chute
- Plastic Pipe Discharge in varying lengths **
- Tub Extension Kit to increase Tub Height

**1000 rpm needed



Technical specifications:	KD 806 Mounted	KD 806 Trailed	KD 807 Mounted	KD 806 Trailed
Overall height	1.87 m	1.94 m	1.87 m	1.94 m
Overall length	2.70 m	3.58 m	2.70 m	3.58 m
Overall width	2.03 m		2.22 m	
Weight	790 kg	1741 kg	810 kg	1786 kg
Discharge height	1.00 m	1.90 m	1.00 m	1.90 m
Tub diameter	1.88 m		2.14 m	
Mounting method	3 point linkage(A frame quick hitch)	Fully trailed	3 point linkage(A frame quick hitch)	Fully trailed
Capacity	1 round bale - 1.50 m 10 rectangular bales 1 large rectangular bale *		1 round bale - 1.80 m 16 rectangular bales 1 large rectangular bale	
Power requirement at PTO	45 kW / 50 hp		45 kW / 50 hp	
PTO input speed **	540 rpm/1000 rpm		540 rpm/1000 rpm	
Discharge time (approx)	5 -10 minutes		5 -10 minutes	
Tyre size	6.00 x 9 x 10	10 x 15.3 x 10	6.00 x 9 x 10	10 x 15.3 x 10

Distributor:

Dealer: