

STANDARD EQUIPMENT:

EC safety guards

Oscillant protections

Frame in cast steel

Strengthened chain ASA 80H

Hexagonal transmission shaft 41 mm

Cardan shaft with safety bolt

Extra resistant blades and bolts

Chain box in cast steel with side window for inspection

MOD. "STANDARD" (ST)					
FOR ROWS OF mm 450-500 WORK mm 290-340 (BONNET)					
HP	MODEL	UNITS NR.	ROWS NR.	FRAME m	WEIGHT
35-45	MEn/4ST	4	4	2,00	790
40-55	ME/5ST (3+2)	5	4	2,40	930
50-70	MEn/6ST (4+2)	6	5	3,00	1050
50-70	MEnR/6ST (4+2)	6	5	3,20/2,50	1100
60-80	MEn/7ST (5+2)	7	6	3,20	1000
60-80	MEnR/7ST (5+2)	7	6	3,20/2,50	1050
MOD. "MEDIUM LARGE" (ML)					
FOR ROWS mm 600-650-700 WORK mm 410-460-510 (BONNET)					
30-40	MEn/2ML	2	3	2,00	470
30-40	MEn/3ML	3	-	2,00	670
50-70	MEn/5ML (3+2)	5	4	3,00	970
50-70	MEnR/5ML (3+2)	5	4	3,20/2,50	1030
MOD. "LARGE" (L)					
FOR ROWS OF mm 700-750-800 WORK mm 510-560-610 (BONNET)					
30-45	MEn/2L	2	-	2,20	480
40-60	MEn/3L	3	-	2,20	680
60-80	MEn/5L (3+2)	5	4	3,20	980
60-80	MEnR/5L (3+2)	5	4	3,20/2,50	1040
70-100	MEn/7L (5+2)	7	6	4,60	1250
MOD. "SUPER LARGE" (SL)					
MOD. "SUPER LARGE" (SL) FOR ROWS OF mm 900-950-1000 WORK mm 670-720-770 (BONNET)					
40-60	MEn/2SL	2	2	2,00	550
60-75	MEn/3SL (1+2)	3	3	2,40	750