

STANDARD EQUIPMENT:

EC safety guards

Cardan shaft with safety bolt

High resistant blades and bolts

Hexagonal transmission shaft 41 mm

Strengthened chain ASA 80H

Frame in cast steel

Oscillant protections

Chain box in cast steel with side window for inspection

MOD. "STANDARD" (ST) FOR ROWS OF mm 450-500 WORK mm 290-340 (BONNET)					
HP	MODEL	UNITS NR.	ROWS NR.	FRAME m	WEIGHT
70-90	MSn/6ST (4+2)	5	4	3,00	900
60-90	MSn/7ST (5+2)	7	6	3,20	1020
60-90	MSnR/7ST (5+2)	7	6	3,20/2,50	1070
80-120	MSn/13ST (11+2)	13	12	6,00	1450
90-120	MSnI/13ST (11+2)	13	12	6,00/3,00	2150
MOD. "MEDIUM LARGE" (ML) FOR ROWS OF mm 600-650-700 WORK mm 400-450-500 (BONNET)					
50-60	MSn/3ML	3	-	2,20	620
70-80	MSn/5ML (3+2)	5	4	3,00	900
70-80	MSnR/5ML (3+2)	5	4	3,20/2,50	1000
MOD. "LARGE" (L) FOR ROWS OF mm 700-750-800 WORK mm 510-570-620 (BONNET)					
70-90	MSn/5L (3+2)	5	4	3,20	950
70-90	MSnR/5L (3+2)	5	4	3,20/2,50	1050
90-120	MSn/7L (5+2)	7	6	4,60	1250
90-120	MSnI/7L (5+2)	7	6	4,60/2,50	1300
90-120	MSnI/9L (7+2)	9	8	6,00/3,00	1950
MOD. "SUPER LARGE" (SL) FOR ROWS OF mm 900-950-1000 WORK mm 670-720-770 (BONNET)					
50-70	MSn/2SL	2	2	2,00	530
60-75	MSn/3SL (1+2)	3	3	2,40	710
MOD. "EXTRA LARGE" (XL) FOR ROWS OF mm 1200-1300 WORK mm 1000 (BONNET)					
60-75	MSn/2XL	2	2	2,00	570
MSn/ = fixed frame					
MSnR/ = mechanical folding frame					
MSnI/ = hydraulic folding frame					