

STANDARD EQUIPMENT:

EC safety guards

Wheels with double bearings and dust cover

Adjustable flasks in micrometric width

Wheels with handle on each weeding unit

Parallelogram with adjustable pressure springs

Parallelogram with 4 lubricators and hard metal bushings

FOR SOYA BEAN AND SUGAR BEETS

MOD. (ST) FOR ROWS WIDTH FROM mm 450 TO mm 500

WITH 2 DISCS AND 3 BLADES ON EACH UNIT (WORKING WIDTH 250/350 mm)

N.	ROWS	MODEL	FRAME meters	WEIGHT kg
	mm			
4	450-500	SHF/5ST-D (3+2)	2,40 fixed	360
5	450-500	SHF/6ST-D (4+2)	3,00 fixed	450
5	450-500	SHR/6ST-D (4+2)	FOLDING	460
6	450-500	SHF/7ST-D (5+2)	3,00/3,30 fixed	500
6	450-500	SHR/7ST-D (5+2)	FOLDING	510
8	450-500	SHF/9ST-D (7+2)	4,00 fixed	560
8	450-500	SHR/9ST-D (7+2)	FOLDING	570
8	450-500	SHI/9ST-D (7+2)	HYDRAULIC	590
12	450-500	SHI/13ST-D (11+2)	HYDRAULIC	1020

FOR TOMATOES

MOD. (L) FOR ROWS WIDTH FROM mm 1300 TO mm 1600

WITH 1 DISC AND 4 BLADES ON EACH UNIT (WORKING WIDTH 450/650 mm each unit)

1	1300-1600	SHF/2L-D	2,00	180
3	1300-1600	SHI/6L-D	HYDRAULIC	520
3	1300-1600	SHI/4SL-D (2+2)	HYDRAULIC	480
5	1300-1600	SHI/10L-D	HYDRAULIC	990

FOR MAIZE, SUNFLOWER, ETC.

MOD. (L) FOR ROWS WIDTH FROM mm 700 TO mm 800

WITH 2 DISCS AND 3 BLADES FOR EACH UNIT (WORKING WIDTH 450/550 mm)

-	700-800	SHF/3L-D	2,40 fixed	280
4	700-800	SHR/5L-D (3+2)	FOLDING	380
6	700-750	SHI/7L-D (5+2)	HYDRAULIC	530

SHF/ = fixed frame

SHR/ = mechanical folding frame

SHI/ = hydraulic folding frame